



## CO-WMFE CUSTOMER TERMINATION POINT

The Customer Termination Point is a small wall mountable unit offering the functions of splicing fibre-to-fibre, splicing fibre-to-pigtail and connector patching.

The CTP provides mechanical protection for both the fibre and its components and permits appropriate access while maintaining the highest standards of fibre management.

Available with the patching bulkhead on the outside of the box or, in the extended version, inside the box with a second cover protecting the splice area.

The product is typically located on the wall, under the floor or within the ceiling void on customer's premises.

The units have the following features

- Compact and modular wall-mountable customer termination box for up to 12 fibres in splicing only format or up to 8 connectors in patching format.
- Suitable for splicing cable-to-cable and cable-to-pigtails or a combination of both
- Pre-determined tubes and fibre routing.
- Internal patching facility with separate splice area protection in the extended version.

The patch panel can accommodate

- Connector adapters.
- Ruggedised cord glands to provide the necessary strain relief when using pigtails with connectors outside the box.
- Cable entry/exit possible from the top or bottom of the unit.

# Ordering Information

## CO-WMFE

### CUSTOMER TERMINATION POINT

CO - WMFE - [ ] - [ ] - [ ] - [ ] - [ ] - [ ] - [ ] - [ ]

Enclosure Style					
Customer Termination Point	0	Extended CTP	4		
Number of Cable Entries					
4 cable entries	04	8 Cable entries (CTP splice only type)	08		
Maximum Fibre Capacity					
2 fibres	A	4 fibres	B	6 fibres	C
12 fibres (CTP splice only type)		E			D
Number of fibres loaded					
None	0	2 fibres loaded	1	4 fibres loaded	2
8 fibres loaded	3	6 fibres	A		
Bulkhead Panel Type					
FC/PC or ST/PC	1	SC/PC or E2000	2	LC	3
DIN	5	SC DPX	6	None (CTP splice only)	7
				MU	4
Connector Type					
FC/PC	A	FC/APC	B	FC/UPC	C
SC/APC	E	SC/UPC	F	ST/PC	G
LC/PC	K	MU/PC	L	E2000/PC	M
DIN/PC	P	DIN/APC	Q	FC Cord Gland	S
SC/PC DPX	U	None	X	SC Cord Gland	T
				SC/PC	D
				ST/APC	H
				E2000/APC	N
				FC Cord Gland	T
Security					
No Locks (CTP)	N				
Loading configuration					
Adaptors	A	Cord Glands	C	3 Adaptors & 1x3dB SM Coupler	D
Empty	E	Adaptors, Pigtails & Cord Glands	M	Adaptors & Pigtails	P
Box Type					
Couplers	C	Unloaded/empty closures	U	Splice and Patch	X
Splice	Y	Patch	Z		
Fibre Type					
9/125 & 62.5/125 mix	1	50/125	5	62.5/125	6
9/125	9	Multimode Adaptors Only	M	Empty	X

### Ordering Example

CO - WMFE - 0 04 - D 3 - 2 D - N - P X 9

Customer Termination Point, single lift off screw fit door, with 4 cable entries and SC style bulkhead panel. 8 fibre capacity, loaded with 8 SC/PC adaptors and pigtails, configured for Splice and Patch applications.

Non standard variants may be available, please contact our sales office for details.

All of this information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics' only obligations are those in the Standard Terms and Conditions of Sale of this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition, Tyco Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.

© Copyright Tyco Electronics 2008

Tyco Electronics UK Ltd  
Comacc Division  
Communications House  
Springwood Industrial Estate, Springwood Drive,  
Braintree, Essex. CM7 2GB, United Kingdom  
00 44 (0)1376 334885 tel  
00 44 (0)1376 334883 fax  
www.comacc.co.uk

 **Tyco Electronics**  
Our commitment. Your advantage.